

#### Step 1:

Layout all of the pieces to the frame. You should have:

#### For the 18' x 20' Canopy:

- 12 Female Pipes
- 12 Male Pipes
- 6 Legs (Legs are longer than any other piece).
- 6 Three-Way Connectors
- 3 Four-Way Connectors
- 1 Top 18' x 20'
- 58 Bungee Cords
- 4 Ground Stakes
- 4 Tie Down Straps
- 1 Installation Manual

#### For the 18' x 30' Canopy:

- 17 Female Pipes
- 17 Male Pipes
- 8 Legs (Legs are longer than any other piece).
- 6 Three-Way Connectors
- 6 Four-Way Connectors
- 1 Top 18 x 30
- 72 Bungee Cords
- 4 Ground Stakes
- 4 Tie Down Straps
- 1 Installation Manual

#### Step 2:

Separate legs from other pieces and set them aside.
Assemble one male tube into one female tube and set them aside.
Continue until all male and female pieces are done.
(you will end up with twelve 10 feet Pipes).









Step 3:
Using the three-way connectors, place 2 pipes in slots.

(Fig 1)

Step 4:
Using three-way connector, make "A" shape with pipes.
(Figures 2 & 3)







Step 5: Continue process untill frame is complete.








Step 6: Unroll tent top (Fig 1)

Step 7:
Drape tent top over frame with silver side facing up.
(Figures 2 & 3)





Step 8: Using elastic clips, secure all four corners first (Figures 1 & 2)





Step 9:
Using elastic clips, start securing the sides of the tent top. Go every other one until all anchors are secure.